


# 4-DIMM Add-in Card (CXA-4F1W)

# For the CXL® Standard

SMART's CXA-4F1W is a 4-DIMM AIC, a Type 3 PCIe Gen5 Add-In Card (AIC) utilizing the CXL standard consisting of four DDR5 RDIMMs mounted on a Full Height, Half Length PCIe form factor module. It uses one x16 CXL controller to implement a single x16 CXL port capable of a total bandwidth of 64GB/s.

Each RDIMM socket supports up to 512GB RDIMMs for a maximum memory capacity of 2TB. The CXL Controllers implement "Reliability, Availability, and Serviceability" (RAS) features, advanced analytics, as well as enhanced security features with in-band or side band (SMBus) monitoring capability.

SMART develops CXL Type 3 (CXL.mem) memory products to address the industry's need for more memory per processor core. The CXL interconnect specification allows for a significant expansion of memory form factor options in PCIe or EDSFF form factors.




## **Key Features**

- Host Interface
  - CXL 2.0
  - One x16 ASIC
  - Up to 64GB/s throughput
- Memory Interface
  - 4 x 512GB DDR5 RDIMMs (2TB max)
  - CXL controller supports two channels up to DDR5-4800
  - Each Channel supports 2DPC
- Security Features
  - CXL Link-Level Integrity and Encryption (IDE)
  - AES-256 Encrypted DDR Memory Interface
  - Firmware Authentication, Integrity Check
- RAS Features
  - End-to-end data path integrity with overlapping parity/ECC
  - SECDED ECC support to DDR
  - Reed-Solomon ECC support to DDR
  - Programmable patrol scrub

- Secure boot
- Secure firmware update
- Device personalization/certificates
- Attestation
- Key management
- Firmware encryption
- CXL IDE
- Post-Package Repair (PPR) and on-die Error Check and Scrub (ECS)
- Memory Expansion Applications
  - Accelerated AI and ML Workloads
  - Large In-memory databases
  - Banking, Finance, OLTP
  - Tiered cache for general purpose storage


### System Block Diagram



### **Dimensions**

The 4-slot AIC uses Full Height Half Length PCIe form factor.

Height: 111.15mmLength: 167.52mmWidth: 33.90mm





### **Preliminary Schedule**

■ ES available in February '24

### **Ordering Information**

4-Socket CXL AIC		
SMART Part Number	Description	Configuration
STXPLXXXGMC4RD5	PCIe x8, FHHL	Single-width AIC without DDR5 RDIMMs
STXPL128GMC4RD5	CXL, PCIe x8, 128GB, FHHL	Single-width AIC with four 32GB DDR5 RDIMMs
STXPL256GMC4RD5	CXL, PCIe x8, 256GB, FHHL	Single-width AIC with four 64GB DDR5 RDIMMs
STXPL512GMC4RD5	CXL, PCIe x8, 512GB, FHHL	Single-width AIC with four 128GB DDR5 RDIMMs

Contact: Torry Steed at <a href="mailto:torry.steed@smartm.com">torry.steed@smartm.com</a> for any sales and sampling queries.



For more information, please visit: www.smartm.com

\*Product images are for promotional purposes only. Labels may not be representative of the actual product.

### Headquarters/North America:

T: (+1) 800-956-7627 • T: (+1) 510-623-1231 F: (+1) 510-623-1434 • E: info@smartm.com

### Latin America:

T: (+55) 11 4417-7200 • E: sales.br@smartm.com

#### Asia/Pacific:

T: (+65) 6678-7670 • E: sales.asia@smartm.com

#### **EMEA**

T: (+44) 0 7826-064-745 • E: sales.euro@smartm.com

#### **Customer Service:**

T: (+1) 510-623-1231 • E: customers@smartm.com